ECO PLUS LINE

Inexpensive - for universal use

- Stepless height adjustment
- Integrated cable channel (36 x 36 mm inside)
- 2D joint for tilting the projector in 2 directions, up to ± 20° vertically and ± 10° horizontally
- Fixing points: 138 - 378 mm
- Can hold up to 15 kg
- Scratch-resistant coating
- Easy mounting, partially pre-assembled
- Supplied with screws M3 / M4 / M5 / M6 and distance elements

Kindermann Eco

Kindermann Eco Plus 60 / 100 / 150

- Integrated cable channel

- Stepless height adjustment

- Adjustable arms (patented)

- 2D joint - for tilting the unit in 2 directions

- Various distance elements for height adjustment



Kindermann Eco Plus line - projector mounts for the ceiling

Model	Distance projector / ceiling	Colour	Ref.N o.
KindermannE co	11 cm	metallic silver, RAL 9006	**5878 000 000**
		white, RAL 9003	**5878 000 010**
Kindermann Eco Plus 60	stepless from 40 - 65 cm	metallic silver, RAL 9006	**7420 000 100**
		white, RAL 9003	**7420 000 110**
Kindermann Eco Plus 100	stepless from 60 - 105 cm	metallic silver, RAL 9006	**5877 000 100**
		white, RAL 9003	**5877 000 110**
Kindermann Eco Plus 150	stepless from 104 - 150 cm	metallic silver, RAL 9006	**7440 000 100**
		white, RAL 9003	**7440 000 110**